


A

B

Wendeschneidplatten für CoroMill® 357



C

				P				K				Abmessungen, mm, Zoll						
			Bestellnummer	1030	4220	4230	4240	1020	3040	3220	4220	4230	4240	LE	IC	S	BS	
Mittel		24	357R-2408M-PM	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆	13	24.4	7.94	3.0	
														.512	.961	.313	.118	
Schwer		24	357N-2408M-KH		☆	☆	☆		☆	☆	☆	☆		13	24.4	7.94	3.0	
														.512	.961	.313	.118	

D

Erklärung der Parameter, siehe Seite 3

= Neuer Artikel

Zahnvorschub, f_z

F

Metrische Werte

Bestellnummer	ISO P			ISO K		
	Min.	f_z mm/z Empfehl.	Max.	Min.	f_z mm/z Empfehl.	Max.
357R-2408M-PM	0.20	0.40	0.60	0.20	0.40	0.60
357N-2408M-KH	0.30	0.50	0.70	0.30	0.50	0.70

Zoll-Werte

G

Bestellnummer	ISO P			ISO K		
	Min.	f_z Zoll/z Empfehl.	Max.	Min.	f_z Zoll/z Empfehl.	Max.
357R-2408M-PM	.008	.016	.024	.008	.016	.024
357N-2408M-KH	.012	.020	.028	.012	.020	.028

H

I

J